


Dimensions:

L : 770 mm
H : 530 mm
W: 540 mm



Weight:

78 kg

Hz 50 Hz

V 400/230 V

Air-cooled

Fuel

3000 rpm

Static Frame

CE Conformity

Indicative image.

1 / General description

GENERAL TECHNICAL DATA	Engine	HONDA GX 390
	Alternator	MECCALTE T16F-160
	Frequency	50Hz
	Voltage	400/230 V
	Operation regime	3000 rpm
	Power factor	0,8
	Fuel tank capacity	6,1 l
	Starter	Manual

> Gasoline generator assembled on static / fixed tubular frame.

POWER	PRP (kVA / kW)	7,5 kVA / 6 kW
--------------	----------------	----------------

Regulations

ENVIRONMENTAL CONDITIONS ISO 8528-1:2005 standard: 25°C, 100kPa and 30% relative humidity:

PRIME POWER (PRP): Electrical power data available at variable load for unlimited hours per year. A 10% overload is permissible for 1 hour every 12 hours according to ISO 8528-1:2005.

EMERGENCY STANDBY POWER (ESP): Electrical power data available at variable load in an emergency according to ISO 8528-1:2005.

The DAGARTECH generator has CE marking which includes the following directives:

- 2006/42 Machinery safety
- 2006/95/CE Low Tension
- 2004/108/CE Electromagnetic compatibility
- 2000/14/CE Noise emissions in the environment outdoors.
- 2012/46/UE Measures against emission of gaseous and particulate pollutants from internal combustion engines to be installed in non-road mobile machinery

2 / Engine specifications

Engine general data

Brand/model	HONDA GX 390
Continuous Power (3000 rpm)	6,4 kW
Net Power (3600 rpm)	8,7 kW
Combustible	Fuel
Number of cylinders	1
Cylinder capacity (cc)	390 cc
Compression ratio	8:1
Torque max (Nm)	25,1 Nm (2500 rpm)
Cooling system	Air
Starter	Manual
Fuel tank capacity (l)	6,1 l
Consumption 100% load (l/h)	2,4 l/h
Consumption 75% load (l/h)	1,8 l/h
Autonomy 75% load (h)	3,4 h
Oil capacity (l)	1,1 l

> 4T OHV Air cooled gasoline engine.

3 / Alternator specifications

Alternator general data

Brand/model	MECC ALTE T16F-160
No. poles	2
Insulation class	H
Mechanical protection degree	IP23
Voltage regulator	Regulation for capacitor
PRP power 40°C (kVA)	7,5 kVA
No.phases	3
Power factor (cos φ)	0,8

> Alternator 2-poles, tri-phase, transformer voltage regulation.

4 / Sockets specifications

- > Base Schukko de 16A, 230V.
- > Base 3P+N +T CEE, 16A. 400V.

5 / Optionals

- > Transport kit: wheels

Dimensions (with wheels):

L : 700 mm
H : 730 mm
W : 620 mm

Weight:

80 kg

